

**AMENDMENTS TO THE CLAIMS**

1. (Previously presented) A ceramic electronic component comprising:  
a component body having a surface and comprising a ceramic which comprises semiconductive barium titanate impregnated with a glass, the ceramic having a positive temperature coefficient and a relative density of 90% or less; and  
a pair of spaced electrodes on the surface of the component body.
2. (Original) A ceramic electronic component according to Claim 1, further comprising a protective layer comprising a glass on a surface of the component body.
3. (Original) A ceramic electronic component according to Claim 1, wherein the glass impregnated in the ceramic has a softening point which does not exceed about 1,000°C.
4. (Original) A ceramic electronic component according to Claim 1, wherein the ceramic comprises a stack of a plurality of layers of a semiconductive barium titanate, and at least two internal electrodes disposed in the stack at different interfaces between said layers, each of said two internal electrodes being electrically connected to a different one of the pair of spaced electrodes on the surface of the component body.
5. (Original) A ceramic electronic component according to Claim 4, further comprising a protective layer comprising a glass on a surface of the component body.

6. (Original) A ceramic electronic component according to Claim 5, wherein the glass impregnated in the ceramic has a softening point which does not exceed about 1,000°C.

7. (Original) A ceramic electronic component according to claim 1, wherein the ceramic comprises a barium titanate free of sintering additives.

8. (Original) A ceramic electronic component according to Claim 7, further comprising a protective layer comprising a glass on a surface of the component body.

9. (Original) A ceramic electronic component according to Claim 7, wherein the ceramic comprises a stack of a plurality of layers of said ceramic, and at least two internal electrodes disposed in the stack at different interfaces between said layers, each of said two internal electrodes being electrically connected to a different one of the pair of spaced electrodes on the surface of the component body.

10. (Original) A ceramic electronic component according to Claim 9, further comprising a protective layer comprising a glass on a surface of the component body.

11. (Original) A ceramic electronic component according to Claim 10, wherein the glass impregnated in the ceramic has a softening point which does not exceed about 1,000°C.

12 - 17. (Canceled)